

## DAFTAR PUSTAKA

- [1] T. Istiqomah, W. Ratnayanti, and F. Candra, “Pengembangan Elektrokardiografi (EKG) Portable Sebagai Wujud Teknologi Tepat Guna,” *Japanese J. Crop Sci.*, vol. 27, no. 4, pp. 467–468, 1959.
- [2] R. Lourenço, P. Leite, A. Lourenço, H. Silva, A. Fred, and D. Coutinho, “Experimental apparatus for finger ECG biometrics,” *BIODEVICES 2012 - Proc. Int. Conf. Biomed. Electron. Devices*, pp. 196–200, 2012, doi: 10.5220/0003777701960200.
- [3] A. M. Al-Busaidi and L. Khriji, “Digitally filtered ECG signal using low-cost microcontroller,” *2013 Int. Conf. Control. Decis. Inf. Technol. CoDIT 2013*, pp. 258–263, 2013, doi: 10.1109/CoDIT.2013.6689554.
- [4] M. S. Islam and N. Alajlan, “Augmented-hilbert transform for detecting peaks of a finger-ECG signal,” *IECBES 2014, Conf. Proc. - 2014 IEEE Conf. Biomed. Eng. Sci. “Miri, Where Eng. Med. Biol. Humanit. Meet,”* no. December, pp. 864–867, 2014, doi: 10.1109/IECBES.2014.7047634.
- [5] Z. Shi, Z. Jinshuan, S. Lihuang, and W. Guohua,

“A novel pocket intelligent one lead ECG monitor based on fingers touching,” *Proc. 2009 2nd Int. Congr. Image Signal Process. CISP’09*, pp. 1–3, 2009, doi: 10.1109/CISP.2009.5305698.

- [6] D. Dobrev and I. Daskalov, “Two-electrode biopotential amplifier with current-driven inputs,” *Med. Biol. Eng. Comput.*, vol. 40, no. 1, pp. 122–127, 2002, doi: 10.1007/BF02347705.
- [7] U. L. B. S.A.Benade, “FINGER TOUCH BASED ECG MONITORING,” *Int. J. Res. Eng. Technol.*, vol. 05, no. 07, pp. 263–266, 2016, doi: 10.15623/ijret.2016.0507040.
- [8] A. B. Mbbs, “Portable out-of-hospital electrocardiography : A review of current technologies,” no. September 2017, pp. 129–138, 2018, doi: 10.1002/joa3.12035.
- [9] D. Dobrev, T. Neycheva, and N. Mudrov, “Simple two-electrode biosignal amplifier,” *Med. Biol. Eng. Comput.*, vol. 43, no. 6, pp. 725–730, 2005, doi: 10.1007/BF02430949.
- [10] P. Wangmo, G. Ramyavani, K. S. Iyer, and V. Karthik Raj, “Two electrode ECG and EOG system for monitoring applications,” *Int. J. Innov.*

*Technol. Explor. Eng.*, vol. 8, no. 11, pp. 262–265, 2019, doi: 10.35940/ijitee.K1315.0981119.

- [11] E. M. Spinelli and M. A. Mayosky, “Two-electrode biopotential measurements: Power line interference analysis,” *IEEE Trans. Biomed. Eng.*, vol. 52, no. 8, pp. 1436–1442, 2005, doi: 10.1109/TBME.2005.851488.
- [12] N. J. Fauzani *et al.*, “Two electrodes system: Performance on ECG FECG and EMG detection,” *Proceeding - 2013 IEEE Student Conf. Res. Dev. SCOReD 2013*, no. December, pp. 506–510, 2013, doi: 10.1109/SCOReD.2013.7002642.
- [13] E. Richard and A. D. C. Chan, “Design of a gel-less two-electrode ECG monitor,” in *2010 IEEE International Workshop on Medical Measurements and Applications, MeMeA 2010 - Proceedings*, 2010, no. c, pp. 92–96, doi: 10.1109/MEMEA.2010.5480198.
- [14] T. Le, H. D. Han, T. H. Hoang, V. C. Nguyen, and C. K. Nguyen, “A low cost mobile ECG monitoring device using two active dry electrodes,” in *2016 IEEE 6th International Conference on Communications and Electronics*,

*IEEE ICCE 2016*, 2016, pp. 271–276, doi:

10.1109/CCE.2016.7562648.

- [15] A. Gruetzmann, S. Hansen, and J. Müller, “Novel dry electrodes for ECG monitoring,” *Physiol. Meas.*, vol. 28, no. 11, pp. 1375–1390, 2007, doi: 10.1088/0967-3334/28/11/005.
- [16] E. Jedari, R. Rashidzadeh, M. Mirhassani, and M. Ahmadi, “Two-electrode ECG measurement circuit using a feed-forward CMRR enhancement method,” *Can. Conf. Electr. Comput. Eng.*, pp. 2–5, 2017, doi: 10.1109/CCECE.2017.7946612.
- [17] G. Feng and J. Wei, “The design of low power portable ECG monitor,” *Proc. - 2019 Int. Conf. Electron. Eng. Informatics, EEI 2019*, pp. 239–242, 2019, doi: 10.1109/EEI48997.2019.00059.
- [18] A. Teeramongkonrasmee, P. Somboon, and A. Lek-Uthai, “Performance of a QRS detector on self-collected database using a handheld two-electrode ECG,” in *BMEiCON 2017 - 10th Biomedical Engineering International Conference*, 2017, vol. 2017-Janua, pp. 1–5, doi: 10.1109/BMEiCON.2017.8229137.
- [19] M. A. Ahamed, M. Asraf-Ul-Ahad, M. H. A.

- Sohag, and M. Ahmad, “Development of low cost wireless ECG data acquisition system,” *Proc. 2015 3rd Int. Conf. Adv. Electr. Eng. ICAEE 2015*, pp. 72–75, 2016, doi: 10.1109/ICAEE.2015.7506799.
- [20] S. Srivastava, R. Kumari, and P. Chowdary, “Acquisition of ECG Signal using EPIC Sensor,” *Int. J. Innov. Res. Sci. Eng. Technol.*, vol. 6, no. 3, pp. 4313–4322, 2017, doi: 10.15680/IJIRSET.2017.0603095.
- [21] R. Lourenc, “Experimental apparatus for finger ecg biometrics,” vol. 1, pp. 196–200, 2012, doi: 10.5220/0003777701960200.
- [22] L. Skolastika Yunarni Juita, Her Gumiwang AW, “ARDUINO BASED 3 CHANNEL ECG DESIGN.” 2017.
- [23] M. Moch. Mufid Muzakki, Dr. Ir. H. Bambang G.I., AIM., MM Sari Luthfiyah, SKp, “POLTEKKESBY-Studi-2530-DRAFTSEMINAR.” 2017.
- [24] D. Ramli and Y. Karan, “Anatomi dan Fisiologi Kompleks Mitral,” *J. Kesehat. Andalas*, pp. 103–112, 2018.

- [25] J. Griffith, *Anatomy at a Glance* Omar Faiz & David Moffat, MD. ISBN #0-632-05934-6, Blackwell Science Ltd, Oxford, United Kingdom, 2002, 172 pp, vol. 16. 2003.
- [26] J. Utama, “Electrocardiogram ( ECG ) dengan Noise Reduction Berbasis Wavelet Menggunakan Pemrograman LabVIEW Electrocardiogram ( ECG ) with Noise Reduction Based on Wavelet Using LabVIEW Programming,” no. September, 2018.
- [27] R. M. Rangayyan, *BIOMEDICAL SIGNAL ANALYSIS*. 2002.
- [28] Ha. A. Dian Permana, Mada Sanjaya W.S, “Desain dan Implementasi Perancangan Elektrokardiograf (ekg) Berbasis Bluetooth,” vol. 2, no. 1, pp. 38–46, 2015.
- [29] B. Babusiak, M. Gala, and S. Borik, “Hardware Design of EeG Data Logger,” pp. 514–517, 2014.