

## **Daftar Pustaka**

- [1] M. Rofi, D. Titisari, and B. Utomo, “Waterbath Calibrator with Nine Channels Sensor,” vol. 1, no. 1, pp. 1–6, 2019.
- [2] S. Kolhatkar and A. K. Joshi, “Automatic temperature control technique for a clinical water bath,” *Proc. - 2nd Int. Conf. Comput. Commun. Control Autom. ICCUBEA 2016*, pp. 1–4, 2017.
- [3] L. Indrayani and M. Sasono, “Uji Homogenitas dan Stabilitas Suhu Mini Liquid Bath untuk Kalibrasi Termometer Digital Makanan,” pp. 299–311, 2017.
- [4] A. G. Procedure, F. O. R. Evaluation, O. F. Calibration, and P. T. Measurements, “Cryostat-correction,” pp. 1370–1372, 1997.
- [5] E. U. Max and A. I. Volume, “Development of 12 Channel Temperature Acquisition System for Heat Development of 12 Channel Temperature Acquisition System for Heat Exchanger Using MAX6675 and Arduino Interface,” vol. 1, no. January, 2019.
- [6] R. A. Koestoyer, Y. A. Saleh, and I. Roihan, “A simple method for calibration of temperature sensor

DS18B20 waterproof in oil bath based on Arduino data acquisition system A Simple Method for Calibration of Temperature Sensor DS18B20 Waterproof in Oil Bath Based on Arduino Data Acquisition System,” vol. 020006, 2019.

- [7] P. S. Ke-, “C dan hasil kalibrasi dengan thermometer dihasilkan tingkat kesalahan penggunaan sensor DS18B20 adalah <2% Kata kunci : sensor, suhu, DB18B20, Arduino uno 1.,” 2017.
- [8] A. Z. Febriyanti and P. C. Nugraha, “Temperature Calibrator Using Thermocouple Based on Microcontroller,” vol. 2, no. 1, pp. 13–20, 2020.
- [9] S. N. Syayakti and E. D. Setioningsih, “4 Channel Sterilizer Calibrator,” vol. 1, no. 2, pp. 65–70, 2019.
- [10] H. G. Ariswati, “Five Channel Temperature Calibrator Using Thermocouple Sensors Equipped With Data Storage,” vol. 1, no. 1, pp. 1–5, 2019.
- [11] A. Prihartono, D. Larassati, B. Herlambang, and A. Insani, “Perancangan Dan Pembuatan Sistem Otomatis Water,” pp. 100–101, 2018.
- [12] W. To and T. Thermocouple, “TYPE K THERMOCOUPLE Why To prefer K Type

Thermocouple : - Composition : - Type K  
Insulation Material : - Temperature Range : -.”

- [13] H. H. Shaker, A. A. Saleh, A. H. Ali, and M. A. Elaziz, “Self-Calibrating Enabled Low Cost , Two Channel Type K Thermocouple Interface for Microcontrollers,” pp. 309–312, 2016.
- [14] D. Singh, “Calibration of Thermocouples for Low Temperature Applications,” pp. 23–26, 2016.
- [15] O. Access, “Thermocouples calibration and analysis of the influence of the length of the sensor coating Thermocouples calibration and analysis of the influence of the length of the sensor coating,” 2015.
- [16] N. Octavia, M. M. Maung, and H. M. Tun, “Performance Evaluation of Fuzzy Logic Controller in Water-Bath Temperature Control System,” vol. 3, no. 6, pp. 1623–1629, 2014.
- [17] J. S. Madugu and P. G. Vasira, “Modeling and Performance Evaluation of P , PI , PD and PID Temperature Controller for Water Bath,” pp. 186–200, 2018.
- [18] WHO, “M Ain T E Nan Ce,” *World Health*, 2008.
- [19] T. C. Enclosures, “KAN Guidance Notes,” no. Glk

- 03, pp. 1–8, 2018.
- [20] W. H. O. Vaccine, “Checking the accuracy of temperature control and monitoring devices,” 2014.
  - [21] “Panduan Kalibrasi Oven,” pp. 1–9, 2011.
  - [22] “AS 2853-1986 Enclosures - Temperature-controlled - Performance testing and grading.pdf.”
  - [23] C. Hagart-Alexander, *21 Temperature Measurement*, 4th ed. Elsevier, 2010.
  - [24] S. Idawati Supu, Baso Usman, Selviani Basri, “PENGARUH SUHU TERHADAP PERPINDAHAN PANAS PADA MATERIAL YANG BERBEDA,” vol. 07, no. 1, pp. 62–73, 2016.
  - [25] Mukhamad Awaludin Fahmi, “Journal of Control and Network Systems TEMPERATURE CONTROL TRAINER PADA,” vol. 5, no. 1, pp. 164–176, 2016.
  - [26] N. Inomata, N. Van Toan, and T. Ono, “Liquid thermocouple Liquid thermocouple using thermoelectric ionic liquids,” *IEEE Sensors Lett.*, vol. PP, no. 3, p. 1, 2019.
  - [27] P. Effendrik, G. Joelianto, and H. Sucipto, “Karakterisasi Thermocouple Dengan

Menggunakan Perangkat Lunak Matlab – Simulink,” pp. 133–145, 2014.

- [28] R. Lund, “Temperature measurements using type K thermocouples and the Fluke Helios Plus 2287A data logger,” 2008.
- [29] N. M. Yuliantini, “ALAT PENCATAT TEMPERATUR OTOMATIS MENGGUNAKAN TERMOKOPEL BERBASIS MIKROKONTROLER AT89S51,” vol. 13, no. 1, pp. 29–33, 2012.
- [30] C. Series, “Thermocouple-based Temperature Sensing System for Chemical Cell Inside Micro UAV Device Thermocouple-based Temperature Sensing System for Chemical Cell Inside Micro UAV Device,” 2018.
- [31] T. Range, “to-Digital Converter ( 0 ° C to + 1024 ° C ) MAX6675 Cold-Junction-Compensated K-Thermocouple- to-Digital Converter ( 0 ° C to + 1024 ° C ) Absolute Maximum Ratings.”
- [32] “No Title,” vol. 328.
- [33] “MICROSOFT,” no. June, 2014.