

DAFTAR PUSTAKA

- [1] F. Pan *et al.*, “Time Course of Lung Changes at Chest CT during Recovery from Coronavirus Disease 2019 (COVID-19),” *Radiology*, vol. 295, no. 3, pp. 715–721, Jun. 2020, doi: 10.1148/radiol.2020200370.
- [2] S. Nabavi and S. Bhadra, “A Robust Fusion Method for Motion Artifacts Reduction in Photoplethysmography Signal,” *IEEE Trans. Instrum. Meas.*, vol. 69, no. 12, pp. 9599–9608, Dec. 2020, doi: 10.1109/TIM.2020.3006636.
- [3] A. M. Alqudah, Q. Qananwah, A. M.K Dagamseh, S. Qazan, A. Albadarneh, and A. Alzyout, “Multiple time and spectral analysis techniques for comparing the PhotoPlethysmography to PiezoelectricPlethysmography with electrocardiography,” *Med. Hypotheses*, vol. 143, p. 109870, Oct. 2020, doi: 10.1016/j.mehy.2020.109870.
- [4] P. Valsalan, T. Ahmed, B. Baomar, A. Hussain, and O. Baabood, “IOT BASED HEALTH

MONITORING SYSTEM,” *J. Crit. Rev.*, vol. 7, no. 04, pp. 739–743, Feb. 2020, doi: 10.31838/jcr.07.04.137.

- [5] E. Piuzzi, S. Pisa, E. Pittella, L. Podesta, and S. Sangiovanni, “Low-Cost and Portable Impedance Plethysmography System for the Simultaneous Detection of Respiratory and Heart Activities,” *IEEE Sens. J.*, vol. 19, no. 7, pp. 2735–2746, Apr. 2019, doi: 10.1109/JSEN.2018.2887303.
- [6] A. Q. Javaid *et al.*, “Quantifying and Reducing Motion Artifacts in Wearable Seismocardiogram Measurements During Walking to Assess Left Ventricular Health,” *IEEE Trans. Biomed. Eng.*, vol. 64, no. 6, pp. 1277–1286, Jun. 2017, doi: 10.1109/TBME.2016.2600945.
- [7] G. Kumar, K. Shilpa Maurya, G. Goyal, and A. Professor, “Design and Development of Heart Rate and Temperature Measuring Device Using MATLAB,” in *International Conference on Computer and Communication Engineering*, 2017, vol. 6, no. 5, pp. 11–13, doi: 10.1109/ICCCE.2010.5556841.
- [8] D. Biswas, N. Simoes-Capela, C. Van Hoof, and N.

- Van Helleputte, “Heart Rate Estimation from Wrist-Worn Photoplethysmography: A Review,” *IEEE Sens. J.*, vol. 19, no. 16, pp. 6560–6570, 2019, doi: 10.1109/JSEN.2019.2914166.
- [9] T. Tamura, “Current progress of photoplethysmography and SPO₂ for health monitoring,” *Biomed. Eng. Lett.*, vol. 9, no. 1, pp. 21–36, 2019, doi: 10.1007/s13534-019-00097-w.
- [10] K. Chooruang and P. Mangkalakeeree, “Wireless Heart Rate Monitoring System Using MQTT,” *Procedia Comput. Sci.*, vol. 86, no. March, pp. 160–163, 2016, doi: 10.1016/j.procs.2016.05.045.
- [11] J. B. Bathilde, Y. L. Then, R. Chameera, F. S. Tay, and D. N. A. Zaidel, “Continuous heart rate monitoring system as an IoT edge device,” in *2018 IEEE Sensors Applications Symposium (SAS)*, Mar. 2018, pp. 1–6, doi: 10.1109/SAS.2018.8336777.
- [12] N. Xiao, W. Yu, and X. Han, “Wearable heart rate monitoring intelligent sports bracelet based on Internet of things,” *Meas. J. Int. Meas. Confed.*, vol. 164, p. 108102, 2020, doi: 10.1016/j.measurement.2020.108102.
- [13] D. Zhou, “Design and implementation of heart-rate

monitoring circuit,” *J. Phys. Conf. Ser.*, vol. 1654, no. 1, 2020, doi: 10.1088/1742-6596/1654/1/012002.

- [14] E. A. Z. Hamidi, M. R. Effendi, and F. Ramdani, “Heart rate monitoring system based on website,” *J. Phys. Conf. Ser.*, vol. 1402, no. 4, 2019, doi: 10.1088/1742-6596/1402/4/044003.
- [15] M. Gregoski, A. Vertegel, and F. Treiber, “Photoplethysmograph (PPG) derived heart rate (HR) acquisition using an Android smart phone,” in *Proceedings - Wireless Health 2011, WH'11*, 2011, pp. 5–6, doi: 10.1145/2077546.2077572.
- [16] Sumber and A. Nasution, “Quantifying the Influence of Moving Artifact on the Determination of Pulse Rate Variability (PRV) from the Pulse Oximetry (SpO_2) Signal Measurements,” *Appl. Mech. Mater.*, vol. 771, pp. 204–208, 2015, doi: 10.4028/www.scientific.net/amm.771.204.
- [17] E. Khan, F. Al Hossain, S. Z. Uddin, S. K. Alam, and M. K. Hasan, “A Robust Heart Rate Monitoring Scheme Using Photoplethysmographic Signals Corrupted by Intense Motion Artifacts,” *IEEE Trans. Biomed. Eng.*, vol. 63, no. 3, pp. 550–562,

- 2016, doi: 10.1109/TBME.2015.2466075.
- [18] S. Hanyu and C. Xiaohui, “Motion artifact detection and reduction in PPG signals based on statistics analysis,” in *2017 29th Chinese Control And Decision Conference (CCDC)*, May 2017, pp. 3114–3119, doi: 10.1109/CCDC.2017.7979043.
 - [19] X. An and G. K. Stylios, “Comparison of Motion Artefact Reduction Methods and the Implementation of Adaptive Motion Artefact Reduction in Wearable Electrocardiogram Monitoring,” *Sensors (Switzerland)*, 2020.
 - [20] A. Melvin Johnson, R. Jegan, and X. Anitha Mary, “Performance measures on blood pressure and heart rate measurement from PPG signal for biomedical applications,” *Proc. IEEE Int. Conf. Innov. Electr. Electron. Instrum. Media Technol. ICIEEIMT 2017*, vol. 2017-Janua, pp. 311–315, 2017, doi: 10.1109/ICIEEIMT.2017.8116856.
 - [21] C. Wei, L. Sheng, G. Lihua, C. Yuquan, and P. Min, “Study on conditioning and feature extraction algorithm of photoplethysmography signal for physiological parameters detection,” *Proc. - 4th Int. Congr. Image Signal Process. CISP 2011*, vol. 4,

- pp. 2194–2197, 2011, doi: 10.1109/CISP.2011.6100581.
- [22] S. K. Bashar, D. Han, A. Soni, D. D. McManus, and K. H. Chon, “Developing a novel noise artifact detection algorithm for smartphone PPG signals: Preliminary results,” in *2018 IEEE EMBS International Conference on Biomedical & Health Informatics (BHI)*, Mar. 2018, pp. 79–82, doi: 10.1109/BHI.2018.8333374.
- [23] H. Dubey, R. Kumaresan, and K. Mankodiya, “Harmonic sum-based method for heart rate estimation using PPG signals affected with motion artifacts,” *J. Ambient Intell. Humaniz. Comput.*, vol. 9, no. 1, pp. 137–150, 2018, doi: 10.1007/s12652-016-0422-z.
- [24] R. Couceiro, P. Carvalho, R. P. Paiva, J. Henriques, and J. Muehlsteff, “Detection of motion artifacts in photoplethysmographic signals based on time and period domain analysis,” in *2012 Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, Aug. 2012, no. August 2012, pp. 2603–2606, doi: 10.1109/EMBC.2012.6346497.

- [25] R. Couceiro, P. Carvalho, R. P. Paiva, J. Henriques, and J. Muehlsteff, “Detection of motion artifact patterns in photoplethysmographic signals based on time and period domain analysis,” *Physiol. Meas.*, vol. 35, no. 12, pp. 2369–2388, Dec. 2014, doi: 10.1088/0967-3334/35/12/2369.
- [26] A. Phinyomark, P. Phukpattaranont, and C. Limsakul, “Feature reduction and selection for EMG signal classification,” *Expert Syst. Appl.*, vol. 39, no. 8, pp. 7420–7431, 2012, doi: 10.1016/j.eswa.2012.01.102.
- [27] U. O. Manchester, “Section 4: Design of FIR Filters,” pp. 1–11.
- [28] I. S. C. sidney Burrus, Matteo Frigo, Steven G. Johnson, Markus Pueschel, *Fast Fourier Transforms*. Texas, 2012.
- [29] D. T. Kusuma, “Fast Fourier Transform (FFT) Dalam Transformasi Sinyal Frekuensi Suara Sebagai Upaya Perolehan Average Energy (AE) Musik,” *Petir*, vol. 14, no. 1, pp. 28–35, Oct. 2020, doi: 10.33322/petir.v14i1.1022.
- [30] L. Tan, *Digital Signal Processing Fundamentals and Applications*. USA: Elsevier, 2008.

- [31] M. Z. Lubis, P. N. Batam, and H. Manik, “SIGNAL PROCESSING FOR POWER SPECTRAL DENSITY,” no. March, 2016, doi: 10.13140/RG.2.1.2106.2006.
- [32] C. Altın, “Comparison of Different Time and Frequency Domain Feature Extraction Methods on Elbow Gesture’s EMG,” vol. 4138, no. August, pp. 35–44, 2016.
- [33] DF Robot, “Heart Rate Sensor SKU: SEN0203,” China.
- [34] H. Lee, H. Chung, J. W. Kim, and J. Lee, “Motion artifact identification and removal from wearable reflectance photoplethysmography using piezoelectric transducer,” *IEEE Sens. J.*, 2019.
- [35] Y. Liang, M. Elgendi, Z. Chen, and R. Ward, “Analysis: An optimal filter for short photoplethysmogram signals,” *Sci. Data*, vol. 5, pp. 1–12, 2018, doi: 10.1038/sdata.2018.76.
- [36] Y. Liang, M. Elgendi, Z. Chen, and R. Ward, “Analysis: An optimal filter for short photoplethysmogram signals,” *Sci. Data*, vol. 5, pp. 1–12, 2018, doi: 10.1038/sdata.2018.76.
- [37] S. Senthilnathan, “Usefulness of Correlation

Analysis,” 2019, doi:
dx.doi.org/10.2139/ssrn.3416918.