

## DAFTAR PUSTAKA

- [1] W. I. Gunawan, “Rancang Bangun Waterbath Dengan Sistem Pengontrol Suhu Dinamis Untuk Media Kalibrasi Termometer Batang Sebagai Upaya Meningkatkan Daya Dukung Laboratorium Berbasis ISO/IEC 17025,” *Integr. Lab J.*, vol. 6, no. 1, pp. 43–46, 2018.
- [2] S. Sumardi and B. Untara, “Shaking Water Bath Berbasis Mikrokontroler Atmega 16,” *Med. Tek. J. Tek. Elektromedik Indones.*, vol. 2, no. 1, 2020, doi: 10.18196/mt.020114.
- [3] B. Dai, R. Chen, and R. C. Chen, “Temperature control with fuzzy neural network,” *Proc. - 2017 IEEE 8th Int. Conf. Aware. Sci. Technol. iCAST 2017*, vol. 2018-Janua, no. iCAST, pp. 452–455, 2017, doi: 10.1109/ICAwST.2017.8256499.
- [4] J. C. Mugisha, B. Munyazikwiye, and H. R. Karimi, “Figure 1: Fuzzy Logic Toolbox [10],” pp. 50–55, 2015.
- [5] S. Sutikno and I. Waspada, “Perbandingan Metode

Defuzzifikasi Sistem Kendali Logika Fuzzy Model Mamdani Pada Motor Dc,” *J. Masy. Inform.*, vol. 2, no. 3, pp. 27–38, 2012, doi: 10.14710/jmasif.2.3.27-38.

- [6] N. Hasim, M. S. M. Aras, M. Z. A. Rashid, A. M. Kassim, and S. S. Abdullah, “Development of fuzzy logic water bath temperature controller using MATLAB,” *Proc. - 2012 IEEE Int. Conf. Control Syst. Comput. Eng. ICCSCE 2012*, pp. 11–16, 2012, doi: 10.1109/ICCSCE.2012.6487107.
- [7] I. Prayogo, R. Alfita, and K. A. Wibisono, “Monitoring System for Heart Rate and Body Temperature as an IOT (Internet Of Thing)-Based Patient Health Level Indicator Using the Fuzzy Logic Method Using Android,” *J. Electr. Comput. Eng. TRIAC*, vol. 4, no. 2, 2017, doi: 10.21107/triac.v4i2.3257.
- [8] S.-E. Oltean and M. Dulău, “Design and Simulation of Fuzzy Logic Based Temperature Control for a Plasma Nitriding Process,” *Procedia Technol.*, vol. 19, pp. 569–575, 2015, doi: 10.1016/j.protcy.2015.02.081.

- [9] Febri Indiani, Dyah Titisari, and Lamidi, “Waterbath Design equipped With Temperature Distribution Monitor,” *J. Electron. Electromed. Eng. Med. Informatics*, vol. 1, no. 1, pp. 11–15, 2019, doi: 10.35882/jeeemi.v1i1.3.
- [10] N. I. Khoiron, D. Titisari, and L. Lamidi, “Rancang Bangun Waterbath Dilengkapi Pemantauan Distribusi Suhu,” *J. Teknokes*, vol. 12, no. 2, pp. 9–14, 2019, doi: 10.35882/teknokes.v12i2.2.
- [11] I. N. B. Hartawan and I. G. M. N. Desnanjaya, “Performance Analysis of Zigbee Protocol Indoors and Outdoors as a Data Communication Media in Wireless Sensor Networks,” *Resist. J. (Computer Syst. Eng.)*, vol. 1, no. 2, pp. 65–72, 2018, doi: 10.31598/jurnalresistor.v1i2.320.
- [12] M. Hong and J. W. Rozenblit, “An Adaptive Force Guidance System for Computer-Guided Laparoscopy Training,” *IEEE Trans. Cybern.*, pp. 1–13, 2021, doi: 10.1109/TCYB.2021.3051837.
- [13] P. Dengan and M. Metode, “38-Article Text-43-1-

10-20180414,” vol. 10, no. 1, 2017.

- [14] J. A. Rodger, “Advances in multisensor information fusion: A Markov–Kalman viscosity fuzzy statistical predictor for analysis of oxygen flow, diffusion, speed, temperature, and time metrics in CPAP,” *Expert Syst.*, vol. 35, no. 4, pp. 1–21, 2018, doi: 10.1111/exsy.12270.
- [15] Mustangin and S. Indra, “Perancangan Modifikasi Heater dan Sistem Kontrol Water Bath Kapasitas 9 Liter 240,” *Semin. Rekayasa Teknol.*, pp. 235–245, 2018.
- [16] M. Rofi’i, S. Syaifudin, D. Titisari, and B. Utomo, “Waterbath Calibrator with Nine Channels Sensor,” *Indones. J. Electron. Electromed. Eng. Med. informatics*, vol. 1, no. 1, pp. 1–6, 2019, doi: 10.35882/ijeeemi.v1i1.1.
- [17] N. Anita, B. Admadi H, and I. Arnata, “Optimasi Konsentrasi Enzim Amiloglukosidase dan Saccharomyces cerevisiae dalam Pembuatan Bioetanol dari Ubi Jalar (*Ipomoea batatas L*) Varietas Daya dengan Proses Sakarifikasi

Fermentasi Simultan (SFS)," *J. Rekayasa dan Manaj. Agroindustri*, vol. 3, no. 2, pp. 30–39, 2015.

- [18] P. Bhaskar, J. Immanuel, and Bhagyajyoti, "Design and development of microcontroller based photoacoustic spectrometer," *Sensors and Transducers*, vol. 141, no. 6, pp. 26–34, 2012, doi: 10.9790/1676-1302034146.
- [19] M. A. Boon, A. E. M. Janssen, and K. Van 't Riet, "Effect of temperatdusre ansd esnzyme origin on the enzymatic synthesis of oligosaccharides," *Enzyme Microb. Technol.*, vol. 26, no. 2–4, pp. 271–281, 2000, doi: 10.1016/S0141-0229(99)00167-2.
- [20] Y. Freer and A. Lyon, "Temperature monitoring and control in the newborn baby," *Paediatr. Child Health (Oxford)*., vol. 22, no. 4, pp. 127–130, 2012, doi: 10.1016/j.paed.2011.09.002.
- [21] I. Agusstian, "Dedsign adnd Busild a Posrtble Heart Rate andd Bdody Temperaturse Mosnitor With IoT System," *Amplif. J. Sci. J. Electr.*

*Comput. Eng.*, vol. 9, no. 2, pp. 14s–18, 2019, doi: 10.33369/jamplifier.v9i2.15378.

- [22] R. Septianas, I. Rosihan, and R. A. Koestoyer, “Testing a calibratison smethods for temperature sensors in differenst worksing fsluids,” *J. Adv. Res. Fluid Mech. Therm. Sci.*, vol. 68, no. 2, pp. 84–93, 2020, doi: 10.37934/ARFMTS.68.2.8493.
- [23] E. Riyanto, “Ardusino Bassed Heart Rate and Body Temperaturse Mseasuring Design and Android Smartphonse,” *Sstudent Sci. Publ. Manuscr. Muhammadiyah Univ. Surakarta*, p. 18, 2016.
- [24] Rangga Adsi Firmansyah, Bambang Guruh I, and Sumber, “Monitoring Hseart Rate And Temperature Based On The Internet Of Things,” *J. Electron. Electromed. Eng. Med. Informatics*, vol. 1, no. 2, pp. 1–7, 2019, doi: 10.35882/jeeemi.v1i2.1.
- [25] M. P. A. T. . Meving Oktheresia Yolanda, Triana Rahmawati and Jurusan, ““Analysis of the Accuracy of Calibration Results in the Design of a

Gas Flowmeter Calibrator Using a TFT LCD,””  
*Pros. Semin. Nas. Kesehat. Politek. Kesehat. Kementeri. Kesehatan. Surabaya*, pp. 1–6, 2020.

- [26] A. B. D. Nandiyanto, R. Zaen, R. Oktiani, A. G. Abdullah, and L. S. Riza, “A simple, rapid analysis, portable, low-cost, and Arduino-based spectrophotometer with white LED as a light source for analyzing solution concentration,” *Telkomnika (Telecommunication Comput. Electron. Control.)*, vol. 16, no. 2, pp. 580–585, 2018, doi: 10.12928/TELKOMNIKA.v16i2.7159.
- [27] G. National and H. Pillars, “ARDUINO MEGA,” vol. 2560.